

NO.1

VERTICALLY INTEGRATED COMPANY
WITH GLOBAL OPERATIONS

INDIAN
SOLAR PANEL
MANUFACTURER

29
YEARS

INDUSTRY
EXPERIENCE

500+
MW

EPC PROJECTS
COMMISSIONED

1.7+
GW

MODULES SUPPLIED
GLOBALLY

5,000+
PROJECTS

IN PUMPS, TELECOM
AND ROOFTOP

68+
COUNTRIES

SERVICES THROUGH 280
SALES OFFICES ACROSS
THE GLOBE

1.5
GW

MODULE
MANUFACTURING
CAPACITY



WAAREE SOLAR TUBULAR Battery - Features

- Rugged tubular positive plate construction with PDC grid spine for long life
 - Ultra low maintenance
 - Suitable for frequent cyclic duty under PSOC condition
 - Supplied in ready to use factory charged condition
- Superior cycle life under deep cycle duty
 - Very low self discharge rate under storage
 - Superior Ampere-hour and Watt-hour efficiency
 - Meets IS-13369 & IEC 61427 specification with latest amendments

TECHNICAL SPECIFICATIONS

Model	Nominal Voltage (V)	Nominal Capacity- C10 (Ah @ 27°C) 10 hr (10.8 V)	Overall Dimensions (in mm)			Battery Weight (Kg) ± 5%	Warranty (months)	Terminal Type
			Length ±5mm	Width ±5mm	Height ± 5mm			
12WT040S	12	40	410	172	245	22.5	36	M8 L-Terminal
12WT040SL	12	40	410	172	245	23.0	60	M8 L-Terminal
12WT060S	12	60	410	172	245	26.0	36	M8 L-Terminal
12WT060SL	12	60	410	172	245	27.0	60	M8 L-Terminal
12WT075S	12	75	508	212	286	39.0	36	M8 L-Terminal
12WT075SL	12	75	508	212	286	40.0	60	M8 L-Terminal
12WT100S	12	100	508	212	286	42.5	36	M8 L-Terminal
12WT100SL	12	100	508	212	286	44.0	60	M8 L-Terminal
12WT120S	12	120	505	190	410	54.5	36	M8 L-Terminal
12WT120SL	12	120	505	190	410	56.0	60	M8 L-Terminal
12WT150S	12	150	505	190	410	59.0	36	M8 L-Terminal
12WT150SL	12	150	505	190	410	61.0	60	M8 L-Terminal
12WT200S	12	200	505	190	410	66.0	36	M8 L-Terminal
12WT200SL	12	200	505	190	410	68.5	60	M8 L-Terminal

CHARACTERISTICS

Charging Current	Minimum 10% to Maximum 20% of the Battery Nominal Capacity
Float Voltage*	13.8 ± 0.1 Volt
Boost Voltage*	15.6 ± 0.1 Volt
Low Voltage Cut-off	11.4 ± 0.1 Volt
Low Reconnect Voltage	13.0 ± 0.1 Volt
Temperature Correction Factor	Float: -18mV/°C, Boost: -30mV/°C
Recharge Factor	110% of Discharge Ah
Storage Period	3 months max.
Operating Temperature	-15 to 55°C
Compliance Standard	Generally conforms to IS-13369 Specification (latest amendments)

*Specifications are under continuous improvement & subject to change without prior notice



WAAREE SOLAR TUBULAR Battery - APPLICATIONS



Solar Power
Plants



Roof-top Solar
Power Pack



Street
Lighting



Railway
Signalling




Telecommunication
Power Supply



Offshore
Platform Power
Supply



Rural
Electrification



Home
Lighting

WAAREE ENERGIES LIMITED

Corporate Office:

602, Western Edge -1,
Off. Western Express Highway, Borivali (E),
Mumbai - 400 066, Maharashtra.
Tel: 022 66 44 44 44 Fax: 022 66 44 44 00
waaree@waaree.com



Rahe Roshan Hamara Nation



**SOLAR TUBULAR
Battery**

